

PRODUCT: Innocoat Sealer Prep

SAFETY DATA SHEET (SDS)

SECTION 1: IDENTIFICATION OF SUBSTANCE & COMPANY DETAIL

Product

Product Name Innocoat Sealer Prep
HSNO approval HSR002662
Approval Description Surface Coatings and Colourants (Flammable) Group Standard 2017
UN number 1263

Recommended Uses: Precoat for resealing existing sealed concrete.

Company Details

Company Innovative Coatings NZ Ltd
37 Beach Road
Richmond
Nelson 7020

Phone 022 086 3584
Email info@innovativecoatingsnz.com

EMERGENCY TELEPHONE NUMBER :0800 POISON (0800 764 766)

SECTION 2: HAZARD IDENTIFICATION

This material is hazardous according to health criteria of ERMA New Zealand

HSNO Classes

Hazard Statements

3.1C	H226 Flammable liquid and vapour
6.1E (oral)	H303 May be harmful if swallowed
6.1E (dermal)	H313 May be harmful in contact with skin
6.9 (respiratory irritant)	H335 May cause respiratory irritation
6.3A	H315 Causes skin irritation
6.4A	H320 Causes eye irritation
6.8B	H361 Suspected of damaging fertility or the unborn child
6.9B	H371 May cause damage to central nervous system, liver or kidney
9.1D	H402 Harmful to aquatic life

Symbols:

PRODUCT: Innocoat Sealer Prep
SAFETY DATA SHEET (SDS)
WARNING


Hazard statement:
H226 Flammable liquid and vapour

Prevention Precautionary Statement(s):

P102 Keep out of reach of children
P103 Read label before use
P104 Read Safety Data Sheet before use
P210 Keep away from ignition sources. NO SMOKING
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion proof electrical equipment
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P261 Avoid breathing vapours
P264 Wash hands thoroughly after handling
P270 Do not eat, drink or smoke when using this product
P271 Use only outdoors or in a well-ventilated area
P280 Wear protective gloves/protective clothing/eye/face protection
P309 IF exposed or concerned: Get medical advice/attention

Storage Precautionary Statement(s)

P403 Store in a well-ventilated place
P235 Keep cool



PRODUCT: Innocoat Sealer Prep

SAFETY DATA SHEET (SDS)

SECTION 3: PHYSICAL COMPOSITION

Chemical Entity	CAS No	Proportion
Xylene	1330-20-7	30 - 50%
Acetone	67-64-1	30 - 50%
Methyl Ethyl Ketone	78-93-3	1 - 10%

SECTION 4: FIRST AID MEASURES


IF exposed or concerned: Get medical advice / attention.
If medical advice is needed, have product container or label at hand.
If poisoning occurs, contact a doctor or the National Poison Information Centre.
Phone 0800 764 766 (0800 POISON) (24 hr emergency service)

First Aid measures

- Inhalation:** **If inhaled:** Remove to fresh air and keep at rest in a position comfortable for breathing. Call a doctor or Poison Centre if you feel unwell.
- Skin contact:** **If on skin:** Wash skin thoroughly with soap and water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. If skin irritation occurs: Get medical advice. Wash contaminated clothing before re use.
- Ingestion:** **If swallowed: DO NOT** induce vomiting. Call a doctor or POISON CENTRE. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
- Eye Contact:** **If in eyes:** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if possible. Continue to rinse for at least 10 minutes. If eye irritation persists: Get medical attention

Work place facilities: Eye wash and ready access to running water

Notes for medical personnel: Treat symptomatically.



PRODUCT: Innocoat Sealer Prep

SAFETY DATA SHEET (SDS)

SECTION 5: FIRE FIGHTING MEASURES

Type of Hazard: Flammable liquid and vapor.

Fire Hazard properties: Vapours may form an explosive mixture in air which can be ignited by many sources, ie electrical motors, switches, pilot lights, open flames and static electricity.

Extinguishing media & method: Carbon dioxide, extinguishing powder, foam

Products of combustion: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. May form toxic mixtures in air and may accumulate in sumps or low lying spaces, forming potentially explosive mixtures.

Recommended protective clothing: Self-contained breathing apparatus (SCBA). Non-flammable overalls, gloves, safety boots

Fire Fighting Advice: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool

Hazchem code: 3Y

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures:

- Stop the source of the leak if it is safe to do so.
- Shut off all possible sources of ignition
- Clear area of any unprotected personnel
- Wear protective equipment to prevent skin, eye and respiratory exposure.
- Work up wind or increase ventilation.
- Contain using sand, earth or vermiculite. Do not use sawdust.
- In case of a major spillage alert the Fire Brigade to location and provide a brief description of hazard.
- Prevent spillage from entering drains, sewers or water courses. If this does occur contact the regional authority immediately

Cleanup methods:

- Use absorbent (soil, sand and/or other inert material).
- Collect and seal in properly labelled containers or drums for disposal.
- Mop up and collect any recoverable material into labelled containers for recycling or salvage.
- Recycle containers wherever possible. Dispose of only in accordance with all regulations (see Section13)



PRODUCT: Innocoat Sealer Prep

SAFETY DATA SHEET (SDS)

SECTION 7 HANDLING & STORAGE

Handling Open containers cautiously as contents may be under pressure. Use only in a well-ventilated area. Keep containers sealed when not in use. Wear appropriate protection (see Section 10). Avoid skin and eye contact and inhalation of vapour. It is essential that anyone handling this product maintains a high standard of personal hygiene, i.e. washing hands prior to eating, drinking, smoking or using toilet facilities.

Storage Store in a cool, dry well-ventilated area away from sources of ignition, oxidizing agents, foodstuffs and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected from physical damage. Inspect regularly for deficiencies such as damage and leaks. Containers must bear the name, HazChem code, UN number and flammability warning. Store out of reach of children.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Work place exposure standards Exposure Limits No exposure standards have been established for this material. However, exposure standards for ingredients are stated below:

Substance	STEL(mg/m ³)	STEL(ppm)	TWA(mg/m ³)	TWA(ppm)
Xylene	655	150	350	80

TWA Time-weighted Average airborne concentration over an eight-hour working day, for a five day working week over an entire working life

STEL Short Term Exposure Limit – the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day.

Application in the workplace According to current knowledge these concentrations should neither impair the health, nor cause undue discomfort to, nearly all workers. These exposure standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to, as low a level as is workable. Exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering Controls

Flammable liquid, maintain adequate ventilation at all times. Prevent accumulation of vapours in hollows or sumps. Eliminate any sources of ignition. Elevated temperature or mechanical action may form vapours, mists or fumes, which may

PRODUCT: Innocoat Sealer Prep

SAFETY DATA SHEET (SDS)

require local, exhaust ventilation systems.

Personal Protective Equipment (PPE)

Detail specifications for equipment



Clothing:

Suitable workwear should be worn to protect personal clothing, e.g. cotton overalls buttoned at the neck and wrists. When large quantities are handled PVC plastic or rubber aprons and boots are recommended.



Hand Protection:

Protective gloves are recommended. PVA or Viton/Butyl gloves are recommended. Replace frequently. Check for wear and tear before use. Open cuts or irritated skin should not be exposed to this material



Eye Protection:

Avoid contact with eyes.
Use safety glasses and/or chemical splash goggles if splashes are possible




Respiratory Protection: If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Use a respirator with an organic vapour cartridge and a dust/mist filter. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order.



General hygiene:

It is essential that all who come into contact with this material maintain a high standard of personal hygiene, i.e. washing hands prior to eating, drinking, smoking or using toilet facilities.



PRODUCT: Innocoat Sealer Prep


SAFETY DATA SHEET (SDS)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear viscous liquid with strong solvent odour
Melting Point:	N/A
Vapour Pressure:	Not available
Boiling Point:	56°C
Solubility in water:	Immiscible
Flammability Class:	3C
Extinguishing Media:	Foam, dry chemical, CO2
Specific Gravity:	.908g/ml
Freezing Point:	N/A
Percent Volatile:	77%
Evaporation Rate:	N/A
PH (% in water):	N/A
Flash Point:	-20°C
Auto Ignition Temp:	465°C
Coefficient of cubic expansion:	N/A
Relative vapour Density:	N/A
Decomposition point:	N/A
Viscosity:	15000-2500(cps@25°C)
Electrostatic generation:	N/A
% volatile by volume:	80%
Flammable Limits:	LEL: 1.1% UEL: 6.6%

SECTION 10 STABILITY AND REACTIVITY

Stability of the substance	Stable under normal conditions
Conditions to avoid	Heat, direct sunlight, open flames and other ignition sources. Prevent vapour accumulation.
Material to avoid	Strong alkalis, acids, nitrates and oxidising agents
Hazardous decomposition products	Emits oxides of carbon when heated to decomposition
Hazardous reactions	None known



PRODUCT: Innocoat Sealer Prep

SAFETY DATA SHEET (SDS)

SECTION 11 TOXICOLOGICAL INFORMATION

Summary

If swallowed: can result in nausea, vomiting and central nervous system depression. If the vomit enters the lungs chemical pneumonia or varying degrees of pulmonary injury and possible death may occur.

If in eyes: may cause eye irritation, resulting in pain and conjunctivitis


If on skin: may cause skin irritation, causing redness, swelling or blistering

If inhaled: may cause respiratory irritation with coughing, nausea. Inhalation may also cause central nervous system depression with headaches, dizziness, drowsiness, incoordination

Chronic Toxicity: Prolonged exposure to hydrocarbons can cause nerve damage (CNS) and affect the liver and kidneys

Supporting Data

Acute For Xylene:	Oral LD50 (rat) : >2000 mg/kg
Dermal LD50 (rabbit):	>2000 mg/kg
Inhalation LC50 (rat)	>20 mg/L/4hr
Skin Irritation:	Irritant
Eye Irritation:	Slight irritant, but not sufficient to trigger an EC label
Skin Sensitisation:	Not expected to be a skin sensitizer
Chronic Mutagenicity:	Not mutagenic
Carcinogenicity:	Not a carcinogen
Fertility Impairment:	Not expected to impair fertility
Development Toxicity:	May cause slight fetotoxicity at doses, which are maternally toxic
Human Effects:	Prolonged/repeated contact may cause defatting of the skin, which can lead to dermatitis. Aspiration into lungs may cause chemical pneumonitis, which can be fatal.



PRODUCT: Innocoat Sealer Prep

SAFETY DATA SHEET (SDS)

SECTION 12 ECOLOGICAL INFORMATION

Summary


This mixture is toxic to aquatic organisms, may cause long-term adverse effects in the aquatic Environment. Prevent this material entering waterways, drains and sewers.

Supporting Data

Ecotoxicity:	Harmful to aquatic life.
Fish:	Toxic 1<LC/EC/IC50 <= 10mg/l
Aquatic Invertebrates:	Toxic 1<LC/EC/IC50 <= 10mg/l
Algae:	Toxic 1<LC/EC/IC50 <= 10mg/l
Mobility:	Floats on water. Absorbs to soil and has a low mobility
Persistence/Degradability	Readily degradable. Oxidizes by photochemical reaction in the air
Bio accumulative Potential	Not bioaccumulative
Terrestrial vertebrate	Not considered harmful towards terrestrial vertebrates

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal information	Dispose of waste according to local and national regulations. Labels should not be removed from containers until they have been cleaned.
Relevant information	This is a flammable product and should be treated with care
Container Disposal	Empty containers may contain hazardous residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill for mild steel or incineration for polyethylene containers as appropriate. Do not incinerate closed containers



PRODUCT: Innocoat Sealer Prep

SAFETY DATA SHEET (SDS)

SECTION 14 TRANSPORT INFORMATION

Transport according to NZS 5433 (Transport of Hazardous Substances on Land).
Considered a dangerous good for transport

UN Number:	1263	Proper shipping name	PAINT
Class	3	Packing Group	II
Hazchem Code	2(Y)	Precautions	Flammable

SECTION 15 REGULATORY INFORMATION

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO).

Approval code: HSR002662, Surface Coatings and Colourants (Flammable) Group Std 2017

Specific Workplace Controls (as per HSNO approval referenced to Controls Matrix)

Key workplace requirements are;

SDS	To be available within 10 minutes where product is stored
Labelling	No removal of labels. Original label must be retained
Emergency plan	Required if >10,000L is stored
Approved handler	Not required
Tracking	Not required
Bunding & secondary containment	Required if >10,000L is stored
Signage	Required if >1,000L is stored
Location Test Certificate	Required if >500L (containers>5L), 1,500L (containers< or =5L), 250L (in use) is stored in any one location
Flammable zone	Must be established if >100L closed containers, 25L decanting, 5L (open occasionally), 1L (in use) stored in any one location
Fire Extinguisher	If >500L present

Note: The above workplace requirements apply if only this particular substance is present.

The complete set of controls for a location will depend on the classification and total quantities of Other substances present in that location.

Other Legislation

In New Zealand the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Safety at Work (General Risk and Workplace Management) Regulations 2016 and local Council Rules and Regional Council plans.

